



The experts you need to



Contech is the leader in stormwater solutions, helping engineers, contractors and owners with infrastructure and land development projects throughout North America.

With our responsive team of stormwater experts, local regulatory expertise and flexible solutions, Contech is the trusted partner you can count on for stormwater management solutions.

Your Contech Team



STORMWATER CONSULTANT

It's my job to recommend the best solution to meet permitting requirements.



STORMWATER DESIGN ENGINEER

I work with consultants to design the best approved solution to meet your project's needs.



REGULATORY MANAGER

I understand the local stormwater regulations and what solutions will be approved.



SALES ENGINEER

I make sure our solutions meet the needs of the contractor during construction.



Removing Pollutants using Hydrodynamic Separation

HDS systems play a vital role in protecting our waterways by removing high levels of sediment, trash, debris, and hydrocarbons from stormwater runoff.

Frequently used as end-of-pipe solutions, they are also used to provide stormwater quality treatment in places where space is limited.

HDS systems capture and retain a variety of stormwater pollutants and are very easy to maintain. These two key benefits have resulted in new uses for HDS technologies, such as pretreating detention, Low Impact Development, and green infrastructure practices, as well as other land-based stormwater treatment systems.

Utilize high-performance hydrodynamic separation to effectively remove finer sediment, oil and grease, and floating and sinking debris.








The Cascade Separator® System

Advanced Sediment Capture Technology ...

The Cascade Separator® is the newest innovation in stormwater treatment from Contech. The Cascade Separator was developed by Contech's stormwater experts using advanced modeling tools and Contech's industry leading stormwater laboratory.

This innovative hydrodynamic separator excels at sediment capture and retention while also removing hydrocarbons, trash, and debris from stormwater runoff. What makes the Cascade Separator unique is the use of opposing vortices that enhance particle settling and a unique skirt design that allows for sediment transport into the sump while reducing turbulence and resuspension of previously captured material. These two factors allow the Cascade Separator to treat high flow rates in a small footprint, resulting in an efficient and economical solution for any site.



| FEATURE | BENEFIT |
|--|--|
| Unique skirt design & opposing vortices | Superior TSS removal; reduced system size and costs |
| Inlet area accepts wide range of inlet pipe angles | Design and installation flexibility |
| Accepts multiple inlet pipes * | Eliminates the need for separate junction structure |
| Grate inlet option* | Eliminates the need for a separate grate inlet structure |
| Internal bypass | Eliminates the need for a separate bypass structure |
| Clear access to sump and stored pollutants | Fast, easy maintenance |

^{*} NJDEP testing based on Cascade Separator with one inlet pipe and no grate inlet

Learn More: www.ContechES.com/cascade

SELECT CASCADE APPROVALS

 New Jersey Department of Environmental Protection Certification (NJDEP)

CASCADE MAINTENANCE


Cascade provides unobstructed access to stored pollutants, making it easy to maintain using a vacuum truck, with no requirement to enter the unit.


The CDS® System

Superior Trash Removal ...

The CDS is a hybrid technology that uses a combination of swirl concentration and indirect screening to separate and trap trash, debris, sediment, and hydrocarbons from stormwater runoff.

At the heart of the CDS system is a unique screening technology used to capture and retain trash and debris. The screen face is louvered so that it is smooth in the downstream direction. The effect created is called "Continuous Deflective Separation." The power of the incoming flow is harnessed to continually shear debris off the screen and to direct trash and sediment toward the center of the separation cylinder. This results in a screen that is self-cleaning and provides 100% removal of floatables and neutrally buoyant material debris 4.7 mm or larger, without blinding.





| FEATURE | BENEFIT |
|---|---|
| Captures and retains 100% of floatables and neutrally buoyant debris 4.7 mm or larger | Superior trash removal |
| Self-cleaning screen | Ease of maintenance |
| Isolated storage sump eliminates scour potential | Excellent pollutant retention |
| Internal bypass | Eliminates the need for additional structures |
| Multiple pipe inlets and 90-180° angles | Design flexibility |
| Clear access to sump and stored pollutants | Fast, easy maintenance |

Learn More:

www.ContechES.com/cds

SELECT CDS APPROVALS

- Washington Department of Ecology (GULD)Pretreatment
- Canadian Environmental Technology
 Verification (ETV)
- California Statewide Trash AmendmentsFull Capture System Certified*

^{*} The CDS System has been certified by the California State Water Resources Control Board as a Full Capture System provided that it is sized to treat the peak flow rate from the region specific 1-year, 1-hour design storm, or the peak flow capacity of the corresponding storm drain, whichever is less.



The Vortechs® System


Stormwater Treatment in a Shallow Footprint


Vortechs combines swirl concentration and flow controls into a single treatment unit that captures and retains trash, debris, sediment, and hydrocarbons from stormwater runoff.

The Vortechs system's large swirl chamber and flow controls work together to create a low energy environment, ideal for capturing and retaining particles down to 50 microns.

Vortechs is the ideal solution for sites with high groundwater, bedrock, utility conflicts, or sites with a large volume runoff.

The Vortechs System is approved by the Washington Department of Ecology (GULD) - Pretreatment.






SELECT VORTECHS APPROVALS

- Washington Department of Ecology (GULD)
 - Pretreatment

Learn More: www.ContechES.com/vortechs

| FEATURE | BENEFIT |
|---|---|
| Large swirl chamber | Fine particle removal down to 50 microns |
| Shallow profile – Typical depth below pipe invert is only 3 feet. | Can be used on sites with high groundwater, bedrock, or utility conflicts |
| Unobstructed access to stored pollutants | Fast, easy maintenance |

Design Your Own Hydrodynamic Separator (DYOHDS™)



Learn More: www.ContechES.com/dyohds

Quickly prepare designs for estimates and project meetings ...

Engineers are always looking for new ways to quickly prepare designs for estimates and project meetings. Contech has developed an online tool to help with the hydrodynamic separation product selection process... the Design Your Own Hydrodynamic Separator (DYOHDS $^{\text{\tiny{M}}}$) tool.

This free, online tool fully automates the layout process for identifying the proper hydrodynamic separator for your site. You can create multiple systems for each project while saving all project information for future use.

- Multiple sizing methods available.
- Site-specific questions ensure the selected unit will comply with site constraints.
- Multiple treatment options may be available based on regulations and site parameters.
- Follow up reports contain a site-specific design, sizing summary, standard detail, and specification.

A free, online tool to aid in the selection of a hydrodynamic separation solution.



A partner









Few companies offer the wide range of highquality stormwater resources you can find with us — state-of-the-art products, decades of expertise, and all the maintenance support you need to operate your system cost-effectively.

THE CONTECH WAY

Contech® Engineered Solutions provides innovative, cost-effective site solutions to engineers, contractors, and developers on projects across North America. Our portfolio includes bridges, drainage, erosion control, retaining wall, sanitary sewer and stormwater management products.

TAKE THE NEXT STEP

For more information: www.ContechES.com

NOTHING IN THIS CATALOG SHOULD BE CONSTRUED AS A WARRANTY. APPLICATIONS SUGGESTED HEREIN ARE DESCRIBED ONLY TO HELP READERS MAKE THEIR OWN EVALUATIONS AND DECISIONS, AND ARE NEITHER GUARANTEES NOR WARRANTIES OF SUITABILITY FOR ANY APPLICATION. CONTECH MAKES NO WARRANTY WHATSOEVER, EXPRESS OR IMPLIED, RELATED TO THE APPLICATIONS, MATERIALS, COATINGS, OR PRODUCTS DISCUSSED HEREIN. ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND ALL IMPLIED WARRANTIES OF FITNESS FOR ANY PARTICULAR PUPPOSE ARE DISCLAIMED BY CONTECH. SEE CONTECH'S CONDITIONS OF SALE (AVAILABLE AT WWW.CONTECHES.COM/COS) FOR MORE INFORMATION.



800-338-1122 | www.ContechES.com