


30"Ø HS20 LOAD RATED



30"Ø HS25 LOAD RATED
24"Ø HS20 LOAD RATED

CHECK ONE:

- ☐ CAST-IN COVER
☐ SEPARATE COVER

CHECK ONE:

- ☐ 30"Ø COVER
☐ 24"Ø COVER
☐ 30"Ø GRATE

FABRICATION NOTES:

1. CONCRETE STRENGTH = 4,000 PSI
2. REINFORCING STEEL - ASTM A615, GRADE 60, OR EQUIVALENT WELDED WIRE FABRIC.
3. NICE LIGHT BROOM FINISH FOR UNITS W/ CAST-IN FRAME AND COVER
4. LIFTERS IN SIDE FOR UNITS W/ CAST-IN FRAME AND COVER AND LIFTERS IN TOP SLAB FOR UNITS W/ SEPARATE COVER

GENERAL NOTES:

1. DESIGN LOAD HS20/HS25
2. EARTH COVER = 1' MAX
3. RISER CAP MUST BE ADEQUATELY SUPPORTED WITH PROPER BEDDING AS TO NOT TRANSFER LOADS ONTO RISER.
4. HEAVY PICK WEIGHT = 1,900 LBS

CONTECH
ENGINEERED SOLUTIONS LLC
www.ContechES.com

9025 Centre Pointe Dr., Suite 400, West Chester, OH 45069
800-338-1122 513-645-7000 513-645-7993 FAX

58" OD CMP RISER CAP
UP TO 36" RISERS
PRECASTER: SEALY, TX

CONTECH
CMP DETENTION SYSTEMS

DATE: 04/07/2021

SCALE: NONE

PROJECT No.:

SEQUENCE No.:

DRAWN: TJS

CHECKED: KMR