







CMP SOLUTIONS for Counties & Municipalities



## CMP SOLUTIONS » HEL-COR® AND ULTRA FLO®





With over 100 years of proven performance, Contech corrugated metal pipe (CMP) solutions offer the best combination of pipe strength and economy for culverts and storm sewers. CMP is available in round and pipe-arch shapes up through 144" diameter and can be manufactured with helical, lock-seam construction or annular corrugations with riveted or spot welded seams. A variety of coupling systems are available to meet the project requirements.

**ULTRA FLO®** manufactured by Contech Engineered Solutions is one of the most hydraulically efficient storm sewer systems available because of its smooth interior surface, longer length, fewer joints and prefabricated junctions that include elbows, manholes and catch basins.

Typical applications for CMP include culverts, stormwater detention systems, small bridges, conduits and storm sewers. A wide variety of wall thicknesses (gages), corrugations, diameters and pipe section lengths permit a choice of materials to meet specific job site requirements.

### HEIGHT OF COVER COMPARISON

#### **Features & Benefits**

- Strength of steel
- Ideal in both shallow and deep cover situations
- Higher pipe stiffness keeps pipe round during backfill process
- Long lengths of 40'-50' eliminates joints and speed installation
- Lightweight enables easy handling, installation and use of small equipment
- Prefabricated fittings (e.g. elbows, compound elbows, wyes, tees, bulkheads, fish baffles, stubs, risers and reducers) – speeds construction and eliminates expensive junction boxes
- Durable provides lower cycle life costs
- Economical drainage pipe yields up front savings

## EXAMPLE: 16 GA, 24" DIA. 2% X ½ CMP VS. 24" DIA. HDPE AASHTO LRFD design requires only 12" minimum cover for Corrugated Steel Pipe, unlike the 24" minimum cover required for Thermoplastic Pipe

# HDPE 124 HDPE ALLOWABIE COVER RANGE COV

#### **END SECTIONS**

Contech® End Sections provide a practical, economical and hydraulically superior method of finishing a variety of culvert materials. The lightweight, flexible metal construction of Contech End Sections creates an attractive, durable and erosion-preventing treatment for all sizes of culvert inlets and outlets.

#### **Features & Benefits**

- Increased hydraulics
- Improved appearance
- Cost-effective installation
- Low maintenance
- Prefabricated beveled or step beveled ends for practical end treatment
- Steel flared end sections prevents inlet/outlet erosion

## DURABLE MATERIAL OPTIONS & COATING ALTERNATIVES

- Galvanized Steel
- Aluminized Steel Type 2 (ALT2)
- Polymer Coated
- Aluminum Alloy

## A Variety of Options with Estimated **Service Life of 75** + **Years**

#### ALT2 - More than just a coating

**Aluminized Steel Type 2** offers the best in economy and durability combined. The aluminum oxide barrier forms in both hard and soft water. The aluminum layer is corrosion resistant and provides cathodic protection. And the thick alloy layer is both abrasion resistant and a pit arrestor.

The U.S. Department of Transportation has stated, "Our field studies suggest that in the absence of abrasion, an Aluminized Steel Type 2 pipe may have a service life up to 8.0 times that predicted for galvanized pipe by the California Method. (If only waterside corrosion is considered, the ratio becomes 3.5). This is a very similar result to the previous study by Potter et al., which suggested that the Aluminized Steel Type 2 should last 6.2 times the life predicted for galvanized culvert."





ESTIMATED CMP SERVICE LIFE				
Material	Estimated Pipe Service Life*	Site Environmental Conditions	Maximum FHWA Abrasion Level <sup>1</sup>	
Galvanized CSP (Minimum 16 gage)	25 - 50 Years	6.0 ≤ pH ≤ 10.0 2000 ≤ r ≤ 8000 (ohm-cm) Water Hardness (< 62.5 ppm CaCo₃)	Level #2	
Aluminized Steel Type 2 CSP (Minimum 16 gage)	75+ Years <sup>2</sup>	$5.0 \le pH \le 9.0$ r > 1500 ohm-cm	Level #2	
Polymer Coated CSP (Minimum 16 gage)	100 Years	$5.0 \le pH \le 9.0$ r > 750 ohm-cm		
	75+ Years	$4.0 \le pH \le 9.0$ r > 750 ohm-cm	Level #3	
	50+ Years	$3.0 \le pH \le 12.0$ r > 250 ohm-cm		
Aluminum Alloy	100 Years	$4.0 \le pH \le 9.0$ r > 500 ohm-cm	Levels #1,#2 or #3	

NOTES: <sup>1</sup> Refer to Table 9.3 for definition of FHWA Abrasion Levels.

<sup>2</sup> Under certain circumstances, AK Steel projects expected service life of 100 years.

<sup>\*</sup> In recommended site environmental conditions. Estimated service life guidance provided by National Corrugated Steel Pipe Association (NCSPA).



Contech® Engineered Solutions provides innovative, cost-effective site solutions to engineers, contractors and developers on projects across North America. Our portfolio includes bridges, drainage, erosion control, retaining wall, sanitary sewer and stormwater management products.







#### FOR MORE INFORMATION CALL:

Corporate Office - Ohio (Cincinnati)	513-645-7000
California (Roseville)	800-548-4667
Colorado (Denver)	720-587-2700
Florida (Orlando)	321-348-3520
Maine (Scarborough)	207-885-9830
Maryland (Baltimore)	410-740-8490
Oregon (Portland)	503-258-3180
Texas (Dallas)	972-590-2000

www.ContechES.com | 800-338-1122

NOTHING IN THIS CATALOG SHOULD BE CONSTRUED AS A WARRANTY. APPLICATIONS SUGGESTED HEREIN ARE DESCRIBED ONLY TO HELP READERS MAKE THEIR OWN EVALUATIONS AND DECISIONS, AND ARE NEITHER GUARANTEES NOR WARRANTIES OF SUITABILITY FOR ANY APPLICATION. CONTECH MAKES NO WARRANTY WHATSOEVER, EXPRESS OR IMPLIED, RELATED TO THE APPLICATIONS, MATERIALS, COATINGS, OR PRODUCTS DISCUSSED HEREIN. ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND ALL IMPLIED WARRANTIES OF FITNESS FOR ANY PARTICULAR PURPOSE ARE DISCLAIMED BY CONTECH. SEE CONTECH'S CONDITIONS OF SALE (AVAILABLE AT WWW.CONTECHES.COM/COS) FOR MORE INFORMATION.







